

Positrex)))

Tracking What Moves

GC095

TotalTracker

COMPACT GPS TRACKING DEVICE FOR LONG-TERM MONITORING, INDUCTIVE, USB OR CABLE CHARGING OPTIONS AND SIMPLE MAGNETIC INSTALLATION

USAGE AND CHARACTERISTICS

- » For the tracking and security of trailers, caravans, machinery and construction equipment. Also suitable as an independent GPS unit for the tracking and security of vehicles or motorcycles
- » Localization and tracking at preselected time interval
- » Monitoring of temperature, acceleration, vibrations, tilting
- » G-shock detection
- » Monitoring of analog input values
- » Monitoring of binary input state - on/off
- » Easy installation by extremely strong magnets
- » Option of screw fixed installation
- » Charging by cable or inductive charging
- » Battery life up to 24 months

MEASURES AND TRANSMITS

- » Exact position of GPS satellite system
- » GSM cell ID and strength of GSM signal
- » Speed and direction of movement
- » Temperature, air pressure, humidity, altitude
- » Tilting – removal detection
- » Battery voltage and status
- » G-shock alert
- » Analogue input voltage
- » Binary input status
- » Vibration histogram and vibration frequency analyzes



TYPES AVAILABLE

TYP	GSM	BATTERY	CHARGING	INPUT
GC 095 243	2G	7 800 mAh	USB	x
GC 095 253	2G	7 800 mAh	cable	1 x analog / 1 x binary
GC 095 263	2G	7 800 mAh	inductive	x
GC 095 043	2G/3G	7 800 mAh	USB	x
GC 095 053	2G/3G	7 800 mAh	cable	1 x analog / 1 x binary
GC 095 063	2G/3G	7 800 mAh	inductive	x

GC095 TotalTracker

COMPACT GPS TRACKING DEVICE FOR LONG-TERM MONITORING, INDUCTIVE, USB OR CABLE CHARGING OPTIONS AND SIMPLE MAGNETIC INSTALLATION

ACCESSORIES

SA 092 000	USB charger 2A (including cable)
SA 095 077	USB charger 2A (incl. cable and inductive charging pad)

TECHNICAL PARAMETERS

GSM	QuadBand 2G – 3G	850/900/1800/1900 MHz – 850/900/1800/1900/2100 MHz
	SIM	Micro Sim, Plug -in 1.8 V
	Types of communication	Calling, SMS, GSM Data, GPRS
	Calls	Alarm call
	SMS	Alarm&Info SMS; SMS commands, requests, SMS configuration
	GPRS internet connectivity	Class 12/static & dynamic IP VPN, UDP protocol / 128bit security encryption key / FW upgrade, configuration settings, on-line value reading, report memory reading, control
GNSS	GPS and Glonass	66 satellites
ANTENNAS	GPS and GSM	Internal
BATTERIES	Type and Capacity	Lilon 7 800 mAh rechargeable
CONSUMPTION	Standby	0.2 mAh continuously 24 hours per day
	Sending of GPS position to server	0.6 mAh single shot
	Self-discharge of battery	0.6 mAh continuously (temp. 15 °C – 25 °C)
INPUTS	Charging by cable*	Charging 8-35 V / max. 1 A@8 V
	Inductive charging**	USB charger 2A with cable and inductive charging pad – see accessories
	USB micro ***	USB charger 2A - see accessories
	Analog*	Analog value 0-30 V
	Binary*	Binary value (log0 = 0-4 V, Log 1 = 5 – 30 V)
SENSORS	3 dimensions G sensor	Movement detection / tilt detection / vibration histogram / G-shock
	Other sensors	Temperature / humidity / air pressure
RF SENSOR INTER-FACE	2,4 MHz	Temperature, humidity, G-shock, magnetic, light
INTERNAL MEMORY	Flash 512 kB	Capacity 5 000 events or GPS positions
DIMENSIONS	Plastic box	120 x 80 x 24 mm
TEMPERATURE RANGE	Lilon rechargeable batteries	-25 °C up to +70 °C, charging 0 °C up to +70 °C
PROTECTION CLASS	IP65	Waterproof
WEIGHT	With batteries	0.22 Kg

* For types with cable only

** For types with inductive charging

*** For types with USB charging

BATTERY LIFE FOR PRESELECTED TRACKING MODE



Expected conditions: > GPS and GSM signals have no significant obstacles
> Temperature in range from 15°C up to 25°C



Plhovska 1997, 547 01
Nachod, Czech republic

tel: +420 491 446 611
fax: +420 491 446 644
email: level@level.systems

Data Box ID: tsjdcq
IČ: 474 69 374
DIČ: CZ 474 69 374

www.positrex.com
C 2701 District court
Hradec Kralove

